




PROJECT NAME: _____ CAT. #: _____
 NOTES: _____ FIXTURE SCHEDULE: _____

MLVT ArcMax Troffer Control Ready Series Wattage and Color Select



Product Description:

ArcMAX™ Lay-In LED troffers are the eye-pleasing and energy efficient replacement for fluorescent troffers in new or remodel construction. CCT and wattage selectable technology enables customers to choose the color temperature and lumen output that is best suited for their lighting application. The troffer's high-performance optic system delivers beautifully even light with excellent color rendering and low glare, while its architectural design features make it the perfect complement to office, education, health care, hospitality and retail interiors.

Features:

- Advanced "UniGlo" optics provides uniform brightness across the lens
- Fixed Wattage and Wattage Selectable Available
- Controls Ready – can be paired with the new cMax controls nodes
- CCT Selectable: 3500K, 4000K, 5000K
- Industry highest efficacy of 150 LPW
- On EM mode, the fixture output a minimum of 1050 lumens for 90 minutes, when fully charged
- 0-10V Dimming

Controls Features:

- Multifunction and Energy Monitoring
- Daylight Sensor
- Occupancy Sensor
- Integral Sensor Receptacle
- High-End Trim
- Bluetooth
- Luminaire Level Lighting Control (LLLC)

Controls Ready:

MaxLite's new Controls Ready (CR) fixtures allows for quick and easy in-field installation (plug and play) of controls. Simply purchase any CR fixture and the required Controls Node and you're all set! See the accessory table for all controls options available for this fixture.



Ordering Structure

FAMILY	SIZE	DIMMABILITY	WATTAGE SELECTABLE	COLOR TEMPERATURE ¹	CON-TROLS	OPTIONS ^{2,3}	PACKAGING	SOURCING STRATEGY
MLVT= ArcMax Troffer	14= 1'x4'	D= Dimmable	13W= 13W, 20W, 26W	CS=Color Selectable (3500K, 4000K, 5000K)	CR=Control Ready	[BLANK]= None E2= Made to order Emergency Back Up EM= Emergency Battery Backup Unit	[BLANK]= None /2PK= 2 pack	[BLANK]= Non-TAA Country TA= TAA Country
	22= 2'x2'		13W= 13W, 20W, 26W					
	24= 2'x4'		22W= 22W, 28W, 34W					
	SIZE	FIXED						
	22= 2'x2'	13=13W						
	24= 2'x4'	19=19W						

¹ Default setting for WCS models is set to lowest wattage and 4000K. Default setting for CS models is set to 4000K.

² Battery back up models are available only in Single Pack configuration.

³ Check the Specification Table for lumen output for EM and E2 suffix.



10-year standard warranty with labor allowance (further details available at www.maxlite.com/warranties)

Warranty Limitations: Product must be rated for application per the Product Data Sheet (PDS); operated ≤16 hrs; in ambient temperatures -4°F to 77°F. If ambient temperatures fall outside the -4°F to 77°F range, product is warranted for 5 years according to the operating temperature range specified on the PDS. Up to \$25/unit; registration required. Additional coverage may be available for purchase; contact MaxLite. Excludes EM/MS versions; component warranty applies.



MLVT ArcMax Troffer Control Ready Series Wattage and Color Select

Accessories (SOLD SEPARATELY)

ORDER CODE	MODEL NUMBER	DESCRIPTION	IMAGE
110788	MLVTP24SMK ¹	ARCMAX 2X4 TROFFER SURFACE MOUNT KIT (L = 48.3inch, W = 24.3inch, H = 4.1inch)	
110787	MLVTP22SMK ¹	ARCMAX 2X2 TROFFER SURFACE MOUNT KIT (L = 24.3inch, W = 24.3inch, H = 4.1inch)	
110786	MLVTP14SMK ¹	ARCMAX 1X4 TROFFER SURFACE MOUNT KIT (L = 48.3inch, W = 12.4inch, H = 4.1inch)	
104816	MLG4CHK	GEN 4 CABLE HANGING KIT FOR 1X4 & 2X2 FLAT PANEL/ TROFFER	
104848	ML24G4CHK	GEN 4 CABLE HANGING KIT FOR 2X4 FLAT PANEL/ TROFFER - 6 CABLES	
104817	ML14G4FK	GEN 4 1X4' FLAT PANEL/ TROFFER FLANGE	
104819	ML22G4FK	GEN 4 2X2' FLAT PANEL/ TROFFER FLANGE KIT	
104820	ML24G4FK	GEN 4 2X4' FLAT PANEL/ TROFFER FLANGE KIT	
c-Max Basic			
105567	CN-REMOTE	CONTROL NODE REMOTE CONTROL	
105890	CN-RTPSW	CONTROL NODE RECTANGULAR, PIR MOTION SENSOR/DAYLIGHT HARVESTING, WHITE	
c-Max Network			
105892	NN-RTW	NETWORK NODE RECTANGULAR, WHITE	
106059	NN-RTPSW	NETWORK NODE RECTANGULAR, PIR MOTION SENSOR/ DAYLIGHT HARVESTING, WHITE	
108392	WNS5-W	5 BUTTON WALL NETWORK SWITCH (BLUETOOTH) WHITE	
106318	NPP-300W	120-277V NETWORK POWER PACK 300W MAX	

¹SMK is compatible with EM and E2 suffix Battery Back up models

Sensor

SENSOR	TECHNOLOGY	DIMMING	DAYLIGHT HARVESTING	REMOTE CONTROL	QR CODE
CN-RTPSW	PIR, Photoelectric	Bi-Level	Continuous Adjustment Mode (CAM)	Yes	
NN-RTW	Bluetooth networking	N/A	N/A	c-Max App (iPhone or Android)	
NN-RTPSW	PIR motion sensing, Photoelectric & Bluetooth networking	Bi-Level	Continuous Adjustment Mode (CAM)	c-Max App (iPhone or Android)	



MLVT ArcMax Troffer Control Ready Series

Wattage and Color Select

Non-TAA Stocked Items

ORDER CODE	MODEL NUMBER	DLC PRODUCT ID#	DLC CLASSIFICATION	DLC CATEGORY
110766	MLVT14D13WCSCR	S-DTZBQ5	Standard	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
110771	MLVT14D13WCSCR/2PK	S-DTZBQ5	Standard	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
110767	MLVT22D13WCSCR	S-2FHSCX	Standard	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
110772	MLVT22D13WCSCR/2PK	S-2FHSCX	Standard	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
110777	MLVT22D13WCSCREM	S-2FHSCX	Standard	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
110768	MLVT24D22WCSCR	S-GS4ML5	Standard	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
		S-LOQ440	Standard	Low-Bay Luminaires for Commercial and Industrial Buildings
110773	MLVT24D22WCSCR/2PK	S-GS4ML5	Standard	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
		S-LOQ440	Standard	Low-Bay Luminaires for Commercial and Industrial Buildings
110778	MLVT24D22WCSCREM	S-GS4ML5	Standard	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
		S-LOQ440	Standard	Low-Bay Luminaires for Commercial and Industrial Buildings

TAA Stocked Items

ORDER CODE	MODEL NUMBER	DLC PRODUCT ID#	DLC CLASSIFICATION	DLC CATEGORY
110985	MLVT14D13WCSCR/2PKTA	S-DTZBQ5	Standard	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
110989	MLVT22D13WCSCR/2PKTA	S-2FHSCX	Standard	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
111485	MLVT22D13WCSCREMTA	S-2FHSCX	Standard	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
110993	MLVT24D22WCSCR/2PKTA	S-GS4ML5	Standard	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
		S-LOQ440	Standard	Low-Bay Luminaires for Commercial and Industrial Buildings
111486	MLVT24D22WCSCREMTA	S-GS4ML5	Standard	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
		S-LOQ440	Standard	Low-Bay Luminaires for Commercial and Industrial Buildings
110987	MLVT22D13CSCR/2PKTA	S-MPVQPX	Standard	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
110991	MLVT24D19CSCR/2PKTA	S-VWZ6YS	Standard	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces



MLVT ArcMax Troffer Control Ready Series

Wattage and Color Select

Specifications

Specifications	MLVT14D13WCSCR		
Size	1x4'		
Nominal Wattage (W)*	13W	20W	26W
Lumens Delivered (lm)*	1950, 2015, 1960	3000, 3100, 3020	3900, 4030, 3920
Nominal Efficacy (lm/W)	150, 155, 151		
Lumens delivered at BBU mode (lm)	1260lm with EM suffix. 1050lm with E2 suffix - for 90 minutes, when fully charged		
CRI	≥80		
Color Temperature (K)*	3500K, 4000K, 5000K		
Calculated L70 Lumen Maintenance	≥100,000 Hrs		
Dimming Technology	0-10V		
Dimming Range	10-100% (Dim to OFF Voltage: 0.3V ± 0.2V)		
Input Voltage	120-277V, 50/60 Hz		
Power Factor	≥ 0.87		
Housing	Sheet Metal		
Diffuser	PMMA lens		
Surge Protection	2.5KV		
Operating Temperature	-4°F to 122°F (-20°C to 50°C), except BBU models. BBU models: 32°F to 122°F (0°C to 50°C)		
Humidity	10% to 80% RH non-condensing		
Certification	ULus listed, FCC, RoHS Compliant		
Qualifications	DLC Standard		
Material Usage	RoHS Compliant; No Mercury		
Environment	Suitable for damp locations		
Warranty	10 years. Check maxlite.com/warranties for details		

* Default setting for WCS models is set to lowest wattage and 4000K



MLVT ArcMax Troffer Control Ready Series

Wattage and Color Select

Specifications

Specifications	MLVT22D13WCSCR			MLVT22D13CSCR
	13W	20W	26W	13W
Size	2x2			
Nominal Wattage (W)*	13W	20W	26W	13W
Lumens Delivered (lm)*	1950, 2010, 1960	3000, 3100, 3020	3900, 4030, 3920	1950, 2010, 1970
Nominal Efficacy (lm/W)	150, 155, 151			150, 155, 152
Lumens delivered at BBU mode (lm)	1260lm with EM suffix. 1050lm with E2 suffix - for 90 minutes, when fully charged			
CRI	≥80			
Color Temperature (K)*	3500K, 4000K, 5000K			
Calculated L70 Lumen Maintenance	≥100,000 Hrs			
Dimming Technology	0-10V			
Dimming Range	10-100% (Dim to OFF Voltage: 0.3V ± 0.2V)			
Input Voltage	120-277V, 50/60 Hz			
Power Factor	≥ 0.87			
Housing	Sheet Metal			
Diffuser	PMMA lens			
Surge Protection	2.5KV			
Operating Temperature	-4°F to 122°F (-20°C to 50°C), except BBU models. BBU models: 32°F to 122°F (0°C to 50°C)			
Humidity	10% to 80% RH non-condensing			
Certification	ULus listed, FCC, RoHs Compliant			
Qualifications	DLC Standard			
Material Usage	RoHS Compliant; No Mercury			
Environment	Suitable for damp locations			
Warranty	10 years. Check maxlite.com/warranties for details			

* Default setting for WCS models is set to lowest wattage and 4000K. Default setting for CS models is set to 4000K.



MLVT ArcMax Troffer Control Ready Series Wattage and Color Select

Specifications

	MLVT24D22WCSCR			MLVT24D19CSCR
Size	2x4			
Nominal Wattage (W)*	22W	28W	34W	19W
Lumens Delivered (lm)*	3430, 3540, 3470	4280, 4420, 4340	5100, 5270, 5160	2880, 2980, 2920
Nominal Efficacy (lm/W)	156, 161, 158	153, 158, 155	150, 155, 152	152, 157, 154
Lumens delivered at BBU mode (lm)	1260lm with EM suffix. 1050lm with E2 suffix - for 90 minutes, when fully charged			
CRI	≥80			
Color Temperature (K)*	3500K, 4000K, 5000K			
Calculated L70 Lumen Maintenance	≥100,000 Hrs			
Dimming Technology	0-10V			
Dimming Range	10-100% (Dim to OFF Voltage: 0.3V ± 0.2V)			
Input Voltage	120-277V, 50/60 Hz			
Power Factor	≥ 0.87			
Housing	Sheet Metal			
Diffuser	PMMA lens			
Surge Protection	2.5KV			
Operating Temperature	-4°F to 122°F (-20°C to 50°C), except BBU models. BBU models: 32°F to 122°F (0°C to 50°C)			
Humidity	10% to 80% RH non-condensing			
Certification	ULus listed, FCC, RoHs Complaint			
Qualifications	DLC Standard			
Material Usage	RoHS Compliant; No Mercury			
Environment	Suitable for damp locations			
Warranty	10 years. Check maxlite.com/warranties for details			

* Default setting for WCS models is set to lowest wattage and 4000K. Default setting for CS models is set to 4000K.

FCC Statement

This device complies with part 15 of the FCC Rules, Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

MLVT ArcMax Troffer Control Ready Series Wattage and Color Select

Product Dimensions

PRODUCT	A (L)	B (W)	C (H)
MLVT14D13WCSCR	47.8 inch	11.7 inch	2 inch
MLVT22D13WCSCR	23.7 inch	23.7 inch	2.1 inch
MLVT22D13CSCR	23.7 inch	23.7 inch	2.1 inch
MLVT24D22WCSCR	47.8 inch	23.7 inch	2.1 inch
MLVT24D19CSCR	47.8 inch	23.7 inch	2.1 inch

